










Hedion Pro LED

Zasilanie / Feed	AC 230V 50/60Hz
Zasilacz / Power supply	Nie
Źródło światła / Light source	-/-
CRI / Color rendering index	-/-
Moc / Power	-/-

HEDION PRO 38 Mounting Ring | 4.3259
HEDION PRO 60 Mounting Ring | 4.3266
HEDION 60 Mounting Ring | 9.1746
HEDION PRO 80 Mounting Ring | 4.3275
HEDION 115 Mounting Ring | 4.2636



Wymiary montażowe Mounting dimensions	Oprowa Frame
Ø55 - H-80	Hedion Pro 38 LC LED
Ø55 - H-150	Hedion Pro 38 HC LED
Ø70 - H-90	Hedion 60 IP65
	Hedion Pro 60 LED (ON-OFF)
	Hedion mini.LED AC230
Ø70 - H-115	Hedion Pro 60 GU10
	Hedion Pro 60 LED (DALI)
	Hedion Pro 60 LED (PhaseCut)
Ø90 - H-110	Hedion 80 Pro LED 12 W
Ø90 - H-175	Hedion 80 Pro LED 25 W
Ø126 - H-90	Hedion 115 QR111
Ø126 - H-95	Hedion 115 edge.LED 6,5W
	Hedion 115 edge.LED 12W
Ø126 - H-125	Hedion 115 edge.LED 25W



NOTE 1 : Do not connect the lighting fixture to the LED driver with the power on !!! Connecting the lighting fitting to the LED driver with the power switched on may damage the LED module and void the warranty.

biuro@labra.pl / export@labra.pl
+48 500 175 552 / www.labra.pl

Zalecane zastosowanie siatki
Recommended use of mesh

Zalecane osadzenie pierścienia montażowego na gipsie zbrojonym.
It's recommended to embed the mounting ring,
on the flexible gypsum putty containing glass fibers.